

## Hangerbolt, Railed

AXE\_AL\_BR\_HB\_RD

### Durable

Non-corrosive materials for the toughest environmental conditions. Strength and integrity testing done.

### Innovative

Adjustable positioning for integration with mounting solutions. Custom J-bolt can be supplied for steel purlins.


### Versatile

Attach to wide variety wooden purlins. Fixation of rails.

### Effortless

Convenient installation with accessible fasteners for saving installation time.

### Dimensions



L 200mm \* W 40mm \*  
H 38mm  
221g

<b>Application</b>	Roof Top – Flush Railed
<b>Roof types</b>	Corrugated, IBR, Asbestos. Wood and metal purlin. Consult for other roof manufacturers
<b>Test protocol</b>	Structural analysis to obtain reaction forces for each possible scenario. Pull tests on clamped bracket FEM analysis on part under load
<b>Materials</b>	<u>Fasteners:</u> Stainless Steel (A2) “Available in Stainless steel (A4)”  <u>Body:</u> L- Bracket: Extruded aluminium (6063 T6) “Anodising available in 25µm layer”  M10 x 200 threaded rod, Stainless Steel  <u>Weatherproof gasket:</u> SVA45 Expanded EVA foam
<b>Certification</b>	ISO 9001
<b>Warranty</b>	10 years <sup>1</sup>

### Integration with Railed system connection

