



AXE^{GM} Ground Mount Exclusive

Durable

Coated steel solution for the toughest environmental conditions.

Innovative

Adjustable tilt from 10 to 20 deg.
Lightweight for ease of installation.

Trust

Conservative coefficient selections in structural design to assure resistance to failure.

Effortless

Innovative design for time-saving installation methods with a modular and practical integrated solution.

Technical

Sway Prevention

Cable brace for increased installation height.

Module Layout

Portrait / Vertical: 1Px3

Module Inclination

10° to 20° angle

Width and Height

Table length up to 3 panels
Lowest panel at maximum 3 meters

Foundation

Planted - Cast into concrete

Materials

Posts, Purlins: Hot-dip galvanised steel (S355)/ZAM310

Small parts: Hot-dip galvanised steel (8.8)

Stainless steel (A2)

Extruded aluminium (6063 T6)

Corrosion Protection

C3: Hot-dip galvanised steel/ZAM310

≥C4: Galvanised steel + duplex coat & zinc flake fasteners

Configurations

1 Portrait/Vertical



Additions

Cable clips to panel frames
End caps for purlins

Standard Features



Aluminium & galvanised steel



Fixed Tilt



Eurocode & SANS Compliant



10 Year Warranty



ISO 9001 Certified